

# Convenient R2R blade label finisher OUT-blade

## 1,000 labels can be cut within one hour without retooling.

Without retooling or cutting, 1,000 labels can be cut within one hour

## The latest technology guarantees the quality of labels.

Consistent levels of label quality can be made by web station applying automated tension control system without tension bar, and blade die-cutting engine.

#### Time and cost can be reduced by "All-in-one process".

A single all-in-one process can perform laminating, die-cutting, the removal of scrap papers, slitting and rewinding simultaneously. Therefore the working time and cost can be saved.

## You will become an export with only a short-term education.

Easy cutting is realized through the simple installation of roll labels and our custom software.

## Make your color labels with short runs, affordable, compact, fast and — it's user-friendly!

## Finishing work is possible in almost all the printed labels.

It supports general large size of label, web width is 350mm and web length is 600mm, and almost all the printed labels from digital label printer or analog web printer.

#### Label with complex images can be cut easily.

Various images ranging from simple circles and rectangles to complex cuts can be executed easily via software.

#### Production is possible without concerns about space.

any-blade does not require a large space. It can be installed or moved in a small space because machine and table are all-in-one and cutting can be done whenever necessary.



### **Specifications**





#### Max web width: 350 mm

• Medium rolls with maximum width of 350mm can be used.



Compact size: 1210 \* 1610 \* 650mm



#### Max cutting speed

Max straight-line cutting speed: 960mm/s.
Max curved-line cutting speed: 600mm/s.



#### **Exclusive software**

Anytron Cut software



#### Max cutting area

• Width 304mm \* length 650mm



Power supply: 220V~240V AC, 50~60Hz



#### Cutting technology: drag knife

Cutting blade type: supersteelSlitting blade type: ultralight blade

• Max down force: 750g



#### General characteristics

- Matrix removal unit, laminating unit, rewinding unit and slitting unit (option).
- Interface: USB
- Registration: using black mark

\* Product specs subject to change without notice



 Shawn
 Cell
 082 467 4694

 Ken
 Cell
 083 774 5292

 Office
 Cell
 087 940 1590

Email shawnbez@nashakele.co.za
Email kenbez@nashakele.co.za
Email info@nashakele.co.za