

This website works best using cookies which are currently enabled. If you continue we'll assume you're OK to receive cookies.
[More about cookie settings](#)



C9655

Full specifications

Printer

A4 Print speed 36ppm colour, 40ppm mono

A3 Print speed 19ppm colour, 21ppm mono

Time to first print (TTFP) 10.5 seconds colour, 9 seconds mono

Warm up time 85 seconds or less from power on

Processor speed PowerPC 750 800MHz

Interface and Software

Connectivity IEEE 1284 Bi-directional Parallel, Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T Ethernet

Printer language PCL5c, PCL XL (Colour), Adobe PostScript 3 with direct PDF Printing (v1.6), SIDM

Network & protocols 10Base-T/100Base-TX/1000Base-T Ethernet Card with internal Web Server for printer and network card set-up and management. TCP/IP:- ARP, RARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, LLTD, JetDirect protocols. Netware 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. EtherTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other: EAP

Advanced networking and security IPv6, 802.1x authentication, SNMPv3, SSL3/TLS HTTPS encryption, Data Encryption, MAC filtering, IP filtering, Secure Erase, Secure Print

OS Compatibility Windows 2000 / XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 R2 / Server 2008 (32-bit & 64-bit) / Vista (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit); Mac OS X (10.3.9 to 10.6.5)

Utility suite Template Manager, Color Correct, OKI LPR, Color Correct Utility, Color Swatch Utility, Color Access Policy Manager, PrintSuperVision.net, PrintSuperVision Java, Print ControlServer, Print Control Client, Print Control Report Tool, Web Driver Installer, ICC Color Profiles, PostScript Gamma Utility, Profile Assistant, PDF Direct Print, Storage Device Manager, ColorSync Profiles, ICC Profiles

Paper Handling

Paper capacity Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 230 sheets of 80gsm

Paper capacity optional tray Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm, High Capacity Feeder: 1,590 sheets of 80gsm (standard on C9655hdtm)

Maximum paper capacity 2,880 sheets of 80gsm

Paper sizes Tray 1/2/3: A3+, A3, A4, A5, A6, Custom size: Width 105 - 328mm Length 148 - 457mm; Multi-purpose tray: A3+, A3, A4, A5, A6, Custom size: Width 76 - 328mm Length 127 - 1,200mm; High Capacity Feeder: A3+, A3, A4, A5, A6, Custom size: Width 105 - 328mm Length 148 - 457mm

Paper weight Tray 1/2/3: 64 to 216gsm; Multi-purpose tray: 64 to 300gsm; Duplex: 64 to 188gsm; High Capacity Feeder: 64 to 216gsm

Duplex Standard: C9655dn/C9655hdn/C9655hdtm; Optional: C9655n

Paper output 500 sheets face down tray, 200 sheets face up tray

Typefaces

Printer fonts 86 scalable PCL fonts, 1 bitmap font, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts

Barcodes Barcode with Checksum support

Print quality

Resolution ProQ2400 Multi-level technology, 1200 x 600dpi

Enhancements Auto Colour Balance, Auto Registration, Auto Media Detect

General Features

Memory (RAM) Standard RAM: 512MB; Maximum RAM: 1024MB

Memory (Hard Disk Drive) Hard Disk Drive: 40GB (Optional on C9655n / C9655dn)

Operating temperature/ humidity 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)

Storage temperature/ humidity -20°C to 45°C, 10% to 90%RH

Power supply Single phase 220 to 240VAC, frequency 50Hz +/- 2Hz

Power consumption Typical: 750W; Max: 1500W; Idle: 200W; Power Save: <26W

Noise level Operating: 54dB(A) or less; Standby: 42dB(A) or less; Power save: 28dB(A) after 30 mins

Dimensions (HxWxD) 471 x 654.5 x 623mm (C9655n, C9655dn, C9655hdn); 873 x 654.5 x 623mm (C9655hdtm)

Weight C9655n: 76kg; C9655dn, C9655hdn: 81kg; C9655hdtm: 133kg

Duty cycle (Maximum) Maximum: 150,000 pages/month

Duty cycle (Recommended) Recommended: 5,000 to 15,000 pages per month

Warranty Free 3 year on-site warranty upon registration within 30 days of purchase. Without registration, the standard pan-European 1 year warranty applies. To register and for T&Cs visit www.oki.co.uk/warranty

EU EMC Directive

Warning! This product complies with EN55022 Class B. However when fitted with optional finisher, inverter or puncher units, compliance to EN55022 is Class A. In a domestic environment this configuration may cause radio interference, in which case the user may be required to take adequate control measures.

