



UV FLATBED PRINTERS

FY-1012



Technical Parameters:

Model		FY-1012B	FY-1012A	FY-1012G
Print Head		SPT 1020 - 12PL	SPT 1020 - 35PL	SPT 1024 GS
Color Configuration		CMYKLcLm + W/ CMYK + W		
Max. Print Width		L 1200mm x W1000mm		
Print Speed*	Standard	18.5m ² /h	16.9m ² /h	25.5m ² /h
	Quality	11.5m ² /h	11m ² /h	16.7m ² /h
	High Quality	8.5m ² /h	7.8m ² /h	12.1m ² /h
Media	Weight	Max. 75kg/m ²		
	Type	Wood, density board, glass metal sheet, PVC, Ceramic Tiles		
	Thickness	Max. 100mm		
RIP Software		ONYX, Ultraprint		
Curing method		LED Lamp		
Ink		UV Curable Ink		
Print interface		USB 2.0		
Power Specification	Printer	AC220V 1000W		
	Flatbed Vacuum Hold Down System	AC220V 1500W		
Operation Environment	Temperature	20° C - 28° C		
	Humidity	40% - 60%		
Dimension		L2470mm x W1750mm x H1450mm	420kg	
Package Size		L2750mm x W1900mm x H1710mm	560kg	
Certificates		CE		

The Speed data are taken from the printer at fast speed. Product specifications are subject to change without notice in advance

Industrial Productivity

High Stability

Low Running Cost

6 Color Printing

- The Choice of personalization printing for art, decor, signage, souvenir and gift
- Professional Inkjet Printing Equipment & Consumables Supplier